Actuator LA36
With endstop reached and absolute positioning Analogue feedback





Connection diagram

36XXXXXXB00/C00XX-XXXXXXXXXXXXXXXXX

		Power	AMP	Deutsch
	BROWN	2	2	2
	BLUE	1		
		Signal	AN	ИР =1
Supply for feedback	+ RED	2		
			Deut	sch
Analogue output	VIOLET	4	6	
Digital output		_		_50
<u>Digital Output</u>	YELLOW	5		
Digital output	GREEN	6		
	CILLIA	J		
Supply for feedback	- BLACK	1		



If you wish to use the endstop signals, you will have to keep power on the Brown, Blue, Red and Black wires, otherwise the signal will be lost.

The signal power must be turned on at all times when the actuator is running, and minimum one second before it starts to run.

I/O specifications

Input/Output	Specification	Comments	
Description	The actuator can be equipped with an electronic circuit that gives an analogue feedback signal when the actuator moves.		
Brown	12 V DC ± 20 %, max. 26 A depending on load 24 V DC ± 10 %, max. 13 A depending on load	To extend actuator: Connect Brown to positive To retract actuator: Connect Brown to negative	
Blue	36 V DC ± 10 %, max. 10 A depending on load 48 V DC ± 10 %, max. 8 A depending on load	To extend actuator: Connect Blue to negative To retract actuator: Connect Blue to positive	
Red	Signal power supply (+) 12 - 36 V DC	Current consumption:	
Black	Signal power supply GND (-)	Max. 60 mA during run and pause There will accure a higher inrush current	
Green	Endstop reached out	Output voltage min. V _{IN} - 2 V Source current max. 100 mA NOT potential free	
Yellow	Endstop reached in		
Violet	Analogue feedback 0-10 V 0.5-4.5 V 4-20 mA	Tolerances +/- 0.2 V or mA Ripple max. 200 mV Transaction delay 20 ms Linear feedback 0.5 % Output: Source Serial resistance: 12 V max 300 ohm 24 V max 900 ohm	
White	Not to be connected		



For actuators with analogue feedback it is recommended to fully extract and retract the actuator on a regular basis (thereby activating the limit switches) in order to ensure precise positioning.

Terms of use

LINAK® takes great care in providing accurate and up-to-date information on its products. However, the user is responsible for determining the suitability of LINAK products for a specific application.

Due to continual development, LINAK products are subject to frequent modifications and changes. LINAK reserves the rights to conduct modifications, updates, and changes without any prior notice. For the same reason, LINAK cannot guarantee the correctness and actual status of imprinted information on its products.

LINAK uses its best efforts to fulfil orders. However, for the reasons mentioned above, LINAK cannot guarantee availability of any particular product at any given time. LINAK reserves the right to discontinue the sale of any product displayed on its website or listed in its catalogues or in other written material created and produced by LINAK, LINAK subsidiaries, or LINAK affiliates.

All sales are subject to the 'Standard Terms of Sale and Delivery for LINAK A/S' available on LINAK websites.

LINAK and the LINAK logotype are registered trademarks of LINAK A/S. All rights reserved.

