MEDLINE[®] CARELINE[®]

Hand Control HD80 Data sheet



LINAK.COM/MEDLINE-CARELINE

HD80

The HD80 makes it possible to have two hand controls in one unit. The hand control is equipped with a magnet locking function, making it possible to have two levels of operation – one for the patient and relatives and one for the caregiver staff. The HD80 provides a great overview using LED indication of functions being locked or unlocked. The hand control is designed to work with OpenBus™ systems.

With the HD80, you get:

- Up to 6 rows of buttons with optional LED indication
- Up to 42 LEDs for indication
- LINAK OpenBus[™] technology
- Intuitive operation
- 2 levels of operation: patient and caregiver level
- LED light

Features and Options:

- Housing colour: Light grey (RAL 7035) Dark grey (RAL 7016)
- Protection class: IPX4 (standard), IPX6 Washable DURA[™]
- Number of buttons: Up to 11 dome keys, 1 magnet key sensor
- Standard or customised • Front cover:
- Cable:
- Coiled 600 mm PU modular plug • Button type: Domes and magnet key sensor.
- For activating the magnet key sensor use the magnet key 0858008
- LED indication: Up to 42 LEDs, option with LED light
- Attachment: Via hook or magnet

Usage:

- Usage temperature:
- Storage temperature: -10 °C to +50 °C
- Compatibility:
- Compatible OpenBus[™] control boxes. Please contact LINAK.
- Relative humidity:
- Atmospheric pressure: 700 to 1060 hPa
- Height above sea level: Max. 3000 meters
- Approvals:


IEC60601-1, ANSI/AAMI ES60601-1 and CAN/CSA-22.2 No 60601-1

20% to 80% - non-condensing

5 °C to 40 °C

Dimensions (mm):

HD80



Hook option




Magnet option

Ordering example:

H	D8	<u>4</u> <u>C</u>	1	0	55	0	0	0	4	 2	0	01	2	001	2	<u>D</u>	<u>1</u>	<u> </u>	0	0	0	-									
																					l		No	ot used		0 = None					
																				L			- No	ot used		0 = None					
																			l				- No	ot used		0 = None					
																							Ca	able type		C = Coiled 60	0 mm				
																							- Ca	able matr.		1 = PU					
																l							- Plu	ug type		D=Modular	Plug 10 Pl	N / 6-	-wires		
																							- Ca	able colour		2 = Grey 3 = Dark Grey	RAL 703 RAL 701				
														L									- SV	V Configurati	ion	xxx= Special L 001= Standar	.ix configu d software	ratior e	ı		
																							- Fu	Inctionality		012 = Standa 01X = Special					
																							- Mo	ounting		0 = Hook M = Magnetic	2				
																							- Co	olour		2 = Grey 3 = Dark Grey	RAL 703 RAL 701				
										 													- IP-	-Degree		4 = IPx4 (Star W = IPX6 Wa		RA™	1		
										 													No	ot used		0 = None					
										 —	—												- No	ot used		0 = None					
										 													- No	ot used		0 = None					
										 													Fro	ont cover nur	mber	The last 3 digi	ts in the fr	ront c	over nu	mber	
										 													Fro	ont cover		J					
										 													- Int	terface		C1 = OpenBu CX = Special	s™ "LIXEI (made by s	DIT" - softwa	· Configi are depa	urable artment)	
										 													- Nu	umber of row	vs	1 = 1 row 2 = 2 rows 3 = 3 rows 4 = 4 rows 5 = 5 rows 6 = 6 rows	Definitic			button n mber of	ows used rows
																							- Co	ontrol type		D8 = HD8x					
L										 													- Co	Controls H = All Hand controls							

Front covers for HD80



Magnet key - article no. 0858008



LINAK® accepts no responsibility for possible errors or inaccuracies in catalogues, brochures, and other material LINAK reserves the right to change its products without prior notice. LINAK cannot guarantee product availability and reserves the right to discontinue the sale of any product. The user's responsible for determining the suitability of LINAK products for a specific application. All sales are subject to the 'Standard Terms of Sale and Delivery', available on LINAK websites.

LINAK and the LINAK logotype are registered trademarks of LINAK A/S. All rights reserved.