

Linear Actuator LA20 Inline Data Sheet



Contents

Introduction.....	3
Features and options	4
Usage	4
Ordering example	5
Dimensions	6
Dimension drawings with extended BID	6
Built-in dimensions	7
Details on piston rod eyes.....	8
Speed and load curves.....	9
Current and load curves	10
Input/output specifications	13
Dual Hall encoded.....	13
Hall potentiometer feedback	13
Motor specification.....	13

Introduction



LA20 is a slim inline actuator created to cover a wide range of applications, where design, size and power are crucial. The combination of a high lifting capacity of 2,500 N with its robust but stylish, small form factor makes the LA20 the ideal solution for many of today's demanding applications.

The actuator is equipped with a socket for exchangeable cables and is to be used with an angled Microfit 30 Deg plug.

Some of the benefits that LA20 Inline offers you:

- Compact and slim design
- High lifting capacity
- Exchangeable cable
- Feedback options for positioning

LA20 is a small inline actuator with a robust design, high efficiency, high lifting capacity at 2500 N, feedback signals for positioning and electrical endstop. It withstands harsh environments within the medical industry.

The LA20 Inline can be used in various applications where space is limited or where size is important.

Features and options

Load in push:	2500 N
Load in pull:	800 N
Dynamic push and pull:	Actuators are designed for push or pull applications. If a combination is required, please contact your local LINAK salesperson.
Housing colour:	Black (RAL 9005), black outer tube, or Light grey (RAL 7035) Black/grey only available as special solution
Protection class:	IPX4, IPX6
Motor:	24VDC, standard motor (type B or G)
Stroke length:	20 – 300 mm (in steps of 1 mm) (Stroke from 201-300 mm will add 20 mm extension)
Built-in dimensions:	170 mm + stroke length (minimum 220 mm)
Mechanical spline:	Yes, as option (will add 20 mm to BID)
Static safety factor:	2.5 in push and 5.0 in pull
Noise level:	Max 58 dB(A) (at nominal voltage and with no load, according to EN ISO 3743-1)
Exchangeable cable:	Yes, LA20 connection plug (Microfit 30 Deg) (Always use cable lock)
Back fixture material:	Solid composite (plastic bushings inside)
Nut:	Guided
Safety nut:	Yes. In pull only for 6 mm spindle pitch
Feedback options:	Dual Hall or Hall potentiometer
Piston rod eye:	Steel Ø22 mm +/- 0,25 mm

Usage

Operation temperature:	+5 °C to +45 °C normal operating temperature -27 °C to +50 °C (according to test conditions ISO 7176-9)
Storage temperature:	-40 °C to +70 °C (according to ISO 7176-9)
Compatibility:	Compatible with LINAK control boxes. Please contact LINAK.
Relative humidity:	20% to 80% – non-condensing
Atmospheric pressure:	700 to 1060 hPa
Meters above sea level:	Max. 3000 meters
Duty cycle:	Max. 10%, 2 minutes continuous use followed by 18 minutes not in use
Cycles:	The LA20 life cycle test has been performed with a stabilised power supply (10% duty cycle) on a 120mm stroke actuator at max. load for 10,000 cycles (at ambient temperature)
Flammability rating:	UL94-V0
Approvals:	IEC60601-1 ANSI/AAMI ES60601-1 CAN/CSA-22.2 No 60601-1 In compliance with ISO 7176-8

Ordering example


Actuator type:	LA	20		
Spindel pitch:	060	025 = 2.5 mm (2500 N) 050 = 5 mm (800 N)	030 = 3 mm (2200 N) 060 = 6 mm (600 N)	040 = 4 mm (1300 N)
Stroke length:	050	xxx = mm (valid from 20 mm to 300 mm)		
Safety:	00	00 = No safety options 0C = Mech. spline without safety nut	0A = Safety nut for Push 0D = Mech. spline with safety nut	0P = Safety nut for pull
Feedback:	00	00 = None (F1)	0A = Hall Potentiometer (F7)	0H = Dual Hall (Digital) (F2) 0M = Dual Hall (Encoded) (F3)
Platform:	0	0 = None		
Motor type:	B	A = 12 VDC (V1) B = 24 VDC (V2) Running mainly with battery (e.g. CBJ1, CBJ2, CBJH, CBJC, CB8A & Customer supplied CB) G = 24 VDC (V3) Running mainly on LINAK CB platforms e.g (CO61, CO71, CO41, CA30/40)		
Endstop:	0	0 = Power switch (E1)	1 = Signal switch (E2)	2 = Encoded (E3)
IP degree:	6	4 = IPx4	6 = IPx6	
Housing colour:	-	- = Black (RAL9005) - black outer tube	+ = Light Grey (RAL7035)	
Back fixture:	0	0 = Ø10.2 mm with plastic bushings	1 = Ø12.3mm without plastic bushings	
Piston rod eye:	0	0 = Steel solid, Ø10.2 mm with plastic bushings 1 = Steel solid, Ø12.3 mm without plastic bushings 2 = Steel with 6.1 mm slot, Ø10.2 mm with plastic bushings (+6,5 BiD)	3 = Steel with 6.1 mm slot, Ø10.2 mm without plastic bushings (+6,5 BiD) 4 = Steel with 6.1 mm slot, Ø12.3 mm without plastic bushings (+6,5 BiD)	
Gear Option:	3	3 = 3 Stage gear, ratio - 1 : 56		
Not Used:	0	0 =		
Safety Factor:	2	1 = 1.5	2 = 2.5	
Not Used:	0	0 =		
Load Direction:	0	0 = Push	P = Pull	
Not Used:	000	000 =		
Installation dimension:	220	xxx = mm (min. installation 220 mm) (extension from 6 mm to 220 mm)		

Chosen item number: 2006005000000806-0030200000220

Note:

- Cable must be ordered separately
- LA20 comes with one cable lock. If extra cable locks are needed they must be ordered separately for LA20 (for item number see later page)
- Noise can occur if plastic bushings are not fitted in the piston rod eye/Back fixture
- Black housing with grey outer tube is available as special solution

Dimensions



Dimension drawings with extended BID


(100 mm stroke without extension and addition of 220 mm extension)

It is possible to order LA20 with extended built-in dimensions.

The total BID cannot exceed 490 mm (incl. extension).

For steps between 1 mm and 5 mm contact LINAK A/S.

For steps of 5 mm use eCon.



Tolerances: For Built-In Dimensions and stroke ± 2 mm.

Drawing No: 1001W4011


Built-in dimensions

The built-in dimension depends on the chosen safety nut and stroke length.

Please see the table below to decide on built-in dimension.

Safety option	Pitch [mm]	Stroke [mm]	Minimum BID [mm]
0 = No safety nut in push/pull	2.5,3,4,5 & 6	20-49	220
		50-200	170 + stroke
		201-300	190 + stroke
1 = Safety nut in push	2.5,3,4,5 & 6	20-40	220
		50-200	170 + stroke
		201-300	190 + stroke
2 = Safety nut Pull	6	20-37	220
		38-200	182 + stroke
		201-300	202 + stroke
3 = Mechanical spline	2.5,3,4 & 5	20-21	220
		22-200	198 + stroke
		201-300	218 + stroke
	6	20-24	220
		30-200	190 + stroke
		201-300	210 + stroke
4 = Mechanical spline + safety nut	2.5,3,4 & 5	20-21	220
		22-200	198 + stroke
		201-300	218 + stroke
	6	20-29	220
		30-200	190 + stroke
		201-300	220 + stroke


A specific stroke length will increase the BID with minimum 6 mm due to installation of a distance bushing that ensures the mechanical endstop to be activated at inwards direction.



Details on piston rod eyes


	Piston rod eyes				
	Picture 1	Picture 2	Picture 3	Picture 4	Picture 5
Specification	Solid No bushings	Solid With bushings	Slot No bushings	Slot With bushings	Slot No bushings
Added BID	-	-	+ 6.5 mm*	+ 6.5 mm*	+ 6.5 mm*
Piston rod eye combiocode	1	0	4	2	3

Picture 1




Piston: 1001W1040
Material: Steel Solid
Bushings: No

Picture 2




Piston: 1001W1040
Material: Steel Solid
Bushings: Yes

Picture 3




Piston: 0231016
Material: Steel
Bushings: No

Picture 4



Piston: 0231016
Material: Steel
Bushings: Yes



Picture 5



Piston: 0231033
Material: Steel
Bushings: No


* Use 7 mm BID for the combiocode

Speed and load curves




Current and load curves


Motor Type A, push




Motor Type A, pull




Motor Type B, push




Motor Type B, pull



Motor Type G, push



Motor Type G, pull



Input/output specifications

Dual Hall positioning

Item	Specification		Comment
Pin configuration	Pin1	GND	
	Pin2	VCC	
	Pin3	M+	
	Pin4	HALL A	
	Pin5	HALL B	
	Pin6	M-	

Dual Hall encoded

Item	Specification		Comment		
Pin configuration	Pin1	External supply: 0 V	Interval	Hall-A	*EOS
	Pin2	VCC	2.65V-3.25V	LOW	NONE
	Pin3	M+ (motor/power)	2.15V-2.65V	HIGH	NONE
	Pin4	HALL A, analogue encoded (Hann-A +EOS* IN/OUT)	1.65V-2.15V	LOW	OUT
	Pin5	HALL B with dual Hall or N/C when testing without dual Hall	1.15V-1.65V	HIGH	OUT
	Pin6	M- (motor/power)	0.65V-1.15V	LOW	IN
			0.05V-0.65V	HIGH	IN

Hall potentiometer feedback

Item	Specification		Comment
Pin configuration	Pin1	External supply: V0	Actuator connector front view:
	Pin2	VCC	
	Pin3	M+ (motor/power)	
	Pin4	Hall potentiometer	
	Pin5	Not connected	
	Pin6	M- (motor/power)	

Motor specification

Item	Specification		Comment
Pin connection	Pin1		Outwards:
	Pin2		
	Pin3	M+/-	Pin3: +
	Pin4		Pin6: -
	Pin5		Inwards:
	Pin6	M-/+	Pin3: -
			Pin6: +

Contacts

FACTORIES

Denmark - Headquarters

LINAK A/S
Phone: +45 73 15 15 15
Fax: +45 74 45 80 48
Fax (Sales): +45 73 15 16 13
Web: www.linak.com

China

LINAK (Shenzhen) Actuator Systems, Ltd.
Phone: +86 755 8610 6656
Phone: +86 755 8610 6990
Web: www.linak.cn

Slovakia

LINAK Slovakia s.r.o.
Phone: +421 51 7563 444
Web: www.linak.sk

Thailand

LINAK APAC Ltd.
Phone: +66 33 265 400
Web: www.linak.com

USA

LINAK U.S. Inc.
Americas Headquarters
Phone: +1 502 253 5595
Fax: +1 502 253 5596
Web: www.linak-us.com
www.linak-latinamerica.com

SUBSIDIARIES

Australia

LINAK Australia Pty. Ltd
Phone: +61 3 8796 9777
Fax: +61 3 8796 9778
E-mail: sales@linak.com.au
Web: www.linak.com.au

Austria

LINAK Zweigniederlassung - Österreich (Wien)
Phone: +43 (1) 890 7446
Fax: +43 (1) 890 744615
E-mail: info@linak.de
Web: www.linak.at - www.linak.hu

Belgium

LINAK Actuator-Systems NV/SA
(Belgium & Luxembourg)
Phone: +32 (0)9 230 01 09
E-mail: beinfo@linak.be
Web: www.linak.be - www.fr.linak.be

Brazil

LINAK Do Brasil Comércio De Atuadores Ltda.
Phone: +55 (11) 2832 7070
Fax: +55 (11) 2832 7060
E-mail: info@linak.com.br
Web: www.linak.com.br

Canada

LINAK Canada Inc.
Phone: +1 502 253 5595
Fax: +1 416 255 7720
E-mail: info@linak.ca
Web: www.linak-us.com

Czech Republic

LINAK C&S s.r.o.
Phone: +42 058 174 1814
Fax: +42 058 170 2452
E-mail: info@linak.cz
Web: www.linak.cz - www.linak.sk

Denmark - International

LINAK International
Phone: +45 73 15 15 15
E-mail: info@linak.com
Web: www.linak.com

Denmark - Sales

LINAK Danmark A/S
Phone: +45 86 80 36 11
Fax: +45 86 82 90 51
E-mail: linak@linak-silkeborg.dk
Web: www.linak.dk

Finland

LINAK OY
Phone: +358 10 841 8700
E-mail: linak@linak.fi
Web: www.linak.fi

France

LINAK France E.U.R.L
Phone: +33 (0) 2 41 36 34 34
Fax: +33 (0) 2 41 36 35 00
E-mail: linak@linak.fr
Web: www.linak.fr

Germany

LINAK GmbH
Phone: +49 6043 9655 0
Fax: +49 6043 9655 60
E-mail: info@linak.de
Web: www.linak.de

India

LINAK A/S India Liaison Office
Phone: +91 120 4531797
Fax: +91 120 4786428
E-mail: info@linak.in
Web: www.linak.in

Ireland

LINAK UK Limited (Ireland)
Phone: +44 (0)121 544 2211
Fax: +44 (0)121 544 2552
+44 (0)796 855 1606 (UK Mobile)
+35 387 634 6554 (Rep.of Ireland Mobile)
E-mail: sales@linak.co.uk
Web: www.linak.co.uk

Italy

LINAK ITALIA S.r.l.
Phone: +39 02 48 46 33 66
Fax: +39 02 48 46 82 52
E-mail: info@linak.it
Web: www.linak.it

Japan

LINAK K.K.
Phone: 81-45-533-0802
Fax: 81-45-533-0803
E-mail: linak@linak.jp
Web: www.linak.jp

Malaysia

LINAK Actuators Sdn. Bhd.
Phone: +60 4 210 6500
Fax: +60 4 226 8901
E-mail: info@linak-asia.com
Web: www.linak.my

Netherlands

LINAK Actuator-Systems B.V.
Phone: +31 76 5 42 44 40 /
+31 76 200 11 10
E-mail: info@linak.nl
Web: www.linak.nl

New Zealand

LINAK New Zealand Ltd
Phone: +64 9580 2071
Fax: +64 9580 2072
E-mail: nzsales@linak.com.au
Web: www.linak.com.au

Norway

LINAK Norge AS
Phone: +47 32 82 90 90
E-mail: info@linak.no
Web: www.linak.no

Poland

LINAK Polska
LINAK Danmark A/S (Spółka Akcyjna)
Phone: +48 22 295 09 70 /
+48 22 295 09 71
E-mail: info@linak.pl
Web: www.linak.pl

Republic of Korea

LINAK Korea Ltd.
Phone: +82 2 6231 1515
Fax: +82 2 6231 1516
E-mail: info@linak.kr
Web: www.linak.kr

Slovakia

LINAK Slovakia S.R.O.
Phone: +421 51 7563 444
Web: www.linak.sk

Spain

LINAK Actuadores, S.L.u
Phone: +34 93 588 27 77
Fax: +34 93 588 27 85
E-mail: esma@linak.es
Web: www.linak.es

Sweden

LINAK Scandinavia AB
Phone: +46 8 732 20 00
Fax: +46 8 732 20 50
E-mail: info@linak.se
Web: www.linak.se

Switzerland

LINAK AG
Phone: +41 43 388 31 88
Fax: +41 43 388 31 87
E-mail: info@linak.ch
Web: www.linak.ch - www.fr.linak.ch
www.it.linak.ch

Taiwan

LINAK (Shenzhen) Actuator systems Ltd.
Taiwan Representative office
Phone: +886 2 272 90068
Fax: +886 2 272 90096
E-mail: sales@linak.com.tw
Web: www.linak.com.tw

Turkey

LINAK İth. İhr. San. ve Tic. A.Ş.
Phone: +90 312 4726338
Fax: +90 312 4726635
E-mail: info@linak.com.tr
Web: www.linak.com.tr

United Kingdom

LINAK UK Limited
Phone: +44 (0)121 544 2211
Fax: +44 (0)121 544 2552
E-mail: sales@linak.co.uk
Web: www.linak.co.uk

DISTRIBUTORS

Argentina

Novotec Argentina SRL
Phone: 011-4303-8989 / 8900
Fax: 011-4032-0184
E-mail: info@novotecargentina.com
Web: www.novotecargentina.com

Colombia

MEM Ltda
Phone: +[57] (1) 334-7666
Fax: +[57] (1) 282-1684
E-mail: servicioalcliente@memltda.com.co
Web: www.mem.net.co

India

Mechatronics Control Equipments India Pvt Ltd
Phone: +91-44-28558484, 85
E-mail: bala@mechatronicscontrol.com
Web: www.mechatronicscontrol.com

Indonesia

PT. Himalaya Everest Jaya
Phone: +6 221 544 8956 /+6 221 544 8965
Fax: +6 221 619 1925
Fax (Sales): +6 221 619 4658
E-mail: hejplastic-div@centrin.net.id
Web: www.hej.co.id

Israel

NetivTech LTD
Phone: +972 55-2266-535
Fax: +972 2-9900-560
Email: info@NetivTech.com
Web: www.netivtech.com

Singapore

Servo Dynamics Pte Ltd
Phone: +65 6844 0288
Fax: +65 6844 0070
E-mail: servodynamics@servo.com.sg

South Africa

Industrial Specialised Applications CC
Phone: +27 011 466 0346
E-mail: gartht@isagroup.co.za
Web: www.isaza.co.za

United Arab Emirates

Mechatronics
Phone: +971 4 267 4311
Fax: +971 4 267 4312
E-mail: mechtron@emirates.net.ae

Terms of use

LINAK® takes great care in providing accurate and up-to-date information on its products. However, the user is responsible for determining the suitability of LINAK products for a specific application. Due to continual development, LINAK products are subject to frequent modifications and changes. LINAK reserves the rights to conduct modifications, updates, and changes without any prior notice. For the same reason, LINAK cannot guarantee the correctness and actual status of imprinted information on its products.

LINAK uses its best efforts to fulfil orders. However, for the reasons mentioned above, LINAK cannot guarantee availability of any particular product at any given time. LINAK reserves the right to discontinue the sale of any product displayed on its website or listed in its catalogues or in other written material created and produced by LINAK, LINAK subsidiaries, or LINAK affiliates. All sales are subject to the 'Standard Terms of Sale and Delivery for LINAK A/S' available on LINAK websites. LINAK and the LINAK logotype are registered trademarks of LINAK A/S. All rights reserved.